



## Double Pallet Handler T429C with bolt-on forks

For 1 pallet or 2 pallets side by side - model 429-4 for 2 or 4 pallets

Model	Capacity kg	LCD mm	S mm	A mm	B mm	D mm	E mm	H mm	G mm	ISO cl.	V mm	CofG Z mm	CofGv Y mm	Weight kg
1,5T 429C	1.600	600	± 100	560-1.720	930	40	80	1.400	1.150	2	145	228	241	438
2T 429C	2.200	600	± 100	560-1.960	1.200	40	80	1.400	1.150 <sup>2)</sup>	2	145	216	245	470
2T 429C	2.500	600	± 100	560-1.960	1.200	50 <sup>1)</sup>	80	1.400	1.150 <sup>2)</sup>	2	145	242	239	518
2T 429C	2.500	600	± 100	560-1.960	1.200	50 <sup>1)</sup>	80	1.400	1.150 <sup>2)</sup>	3	145	238	246	527
2T 429C	2.500	600	± 100	560-2.160	1.400	50 <sup>1)</sup>	80	1.400	1.150 <sup>2)</sup>	2	145	236	240	536
2T 429C	2.500	600	± 100	560-2.160	1.400	50 <sup>1)</sup>	80	1.400	1.150 <sup>2)</sup>	3	145	232	247	545
2T 429C-4	1.250	1.200	± 100	560-1.960	1.200	50	80	1.400	2.400	2	145	550	181	650
2T 429C-4	1.250	1.200	± 100	560-1.960	1.200	50	80	1.400	2.400	3	145	543	188	660
2,5T 429C-4	1.600	1.200	± 100	560-1.960	1.200	60	80	1.400	2.400	3	145	577	181	730
3T 429C	3.200	600	± 100	560-1.960	1.200	60	80	1.400	1.150 <sup>2)</sup>	3	145	256	241	572
3T 429C	3.200	600	± 100	560-2.160	1.400	60	80	1.400	1.150 <sup>2)</sup>	3	145	250	243	590
3T 429C-2	5.000	600	± 100	560-1.960	1.200	60	80	1.400	1.150 <sup>2)</sup>	3	180	246	287	720
3T 429C-2	5.000	600	± 100	560-1.960	1.200	60	80	1.400	1.150 <sup>2)</sup>	4	183	238	288	749
3T 429C-2	5.000	600	± 100	560-1.960	1.400	60	80	1.400	1.150 <sup>2)</sup>	3	180	240	289	748
3T 429C-2	5.000	600	± 100	560-1.960	1.400	60	80	1.400	1.150 <sup>2)</sup>	4	183	233	290	777
3T 429C-4	2.500	1.200	± 100	560-1.960	1.200	60	80	1.400	2.400	3	180	578	220	910
3T 429C-4	2.500	1.200	± 100	560-1.960	1.200	60	80	1.400	2.400	4	183	561	212	940
3T 429C-4	2.500	1.200	± 100	560-1.960	1.400	60	80	1.400	2.400	3	180	563	223	933
3T 429C-4	2.500	1.200	± 100	560-1.960	1.400	60	80	1.400	2.400	4	183	550	215	963
3,5T 429C-4	2.800	1.200	± 100	560-1.960	1.200	60	80	1.400	2.400	3	180	568	221	941
3,5T 429C-4	2.800	1.200	± 100	560-1.960	1.200	60	80	1.400	2.400	4	183	561	212	941
3,5T 429C-4	2.800	1.200	± 100	560-1.960	1.400	60	80	1.400	2.400	3	180	556	224	964
3,5T 429C-4	2.800	1.200	± 100	560-1.960	1.400	60	80	1.400	2.400	4	183	550	215	964
4T 429C-4 <sup>3)</sup>	3.200	1.200	± 160	560-1.960	1.460	60	80	1.400	2.400	4	183	512	237	1.038
4T 429C-4 <sup>3)</sup>	4.600	1.200	± 160	560-1.960	1.460	70	80	1.400	2.400	4	183	536	228	1.111
6T 429-4 <sup>3)</sup>	6.000	1.200	± 160	560-1.960	1.860	75	90	1.400	2.400	4	218	530	205	1.390
6T 429-4 <sup>3)</sup>	6.000	1.200	± 250	560-1.960	1.920	75	90	1.400	2.400	4	218	530	205	1.410

### Preferential range

**i** Measurement „C” = alternatively 560 / 650 / 700 mm mechanically or hydraulically adjustable (solenoid valve required). Measurement „H” = standard height 1.400 mm, other lengths and forms upon request. Pallet retainer lip available upon request. Double solenoid valve for additional individual adjustment for each pair of forks available upon request.

1) Optional with fork thickness 40 mm.

2) Fork length optional 1.000 mm, 1.150 mm or 1.200 mm.

3) Standard with wider fork shanks. For pallet width 1.200 mm we recommend the 1.400 mm wide body version.

